

# Technical Newsletter

#tnl2018-0005e

# 1 / 1



## Ultrasonic-wave Dicing Unit: Change of USW Mount and Securing Bolt





### Notice of change

In order to support the specification of a minimum blade distance of 20 mm, which had been desired by customers, we have changed the USW mount and securing bolt of the ultrasonic-wave dicing unit (user-specified specification). Since January 2018, we have gradually begun to ship the part after change.

### Applicable models for ultrasonic-wave dicing unit

Series	Applicable models
3000 series	DAD3220 DAD3230 DAD3240 DAD3350 DAD3430
6000 series	DFD6240 DFD6340 DFD6341 DFD6361 DFD6362 DFD6560

### Changes

		Before the change	After the change
Supported specification		To a minimum blade distance of 24 mm	To a minimum blade distance of 20 mm
USW mount	Part No.	MUSS-020002-0	MUSS-020003-0
	Appearance	 No distinguishing mark	 6 distinguishing marks "0" are engraved.
Securing bolt (washer)	Part No.	LKBZ-510172-0 (securing bolt) LKBZ-510173-0 (washer)	LUSH-010235-0
	Appearance	 The securing bolt and washer have similar appearances to those of the standard specification.	 The securing bolt is integrated with the washer so that it is easier to be distinguished from that of the standard specification.

- The parts before the change will be discontinued.
- The parts after the change are interchangeable. All the other accessories of the ultrasonic-wave dicing unit can be continually used.
- There is no change in the replacing procedures and the usages of the USW blade and USW mount.

### Inquiries

Please contact your local DISCO sales representative or customer engineer if you have any questions regarding this matter.